



Check List for Scheduled Maintenance



Customer Name:	Model:	Plate number:
Frame number (VIN):	Registration date:	Mileage:
Current date:	Work Order Number:	Service type:

Scheduled Maintenance Check List for Multistrada V4

Check the boxes close to the performed service operations

Performed	Replaced		Annual Service			
			Valve Check			
			Oil Service			
			Oil Service 1000			
<input type="checkbox"/>	<input type="checkbox"/>	Read fault memory with the DDS 3.0 tester, and check technical updates and recall campaigns on DCS	•	•	•	•
<input type="checkbox"/>	<input type="checkbox"/>	Change engine oil and filter	•	•		24
<input type="checkbox"/>	<input type="checkbox"/>	Check and clean air filter		•		
<input type="checkbox"/>	<input type="checkbox"/>	Change air filter				every 30,000km/18,000mi
<input type="checkbox"/>	<input type="checkbox"/>	Check and/or adjust valve clearance			•	
<input type="checkbox"/>	<input type="checkbox"/>	Replace spark plugs			•	
<input type="checkbox"/>	<input type="checkbox"/>	Change coolant			•	48
<input type="checkbox"/>	<input type="checkbox"/>	Change front fork fluid				every 45,000km/27,000mi
<input type="checkbox"/>	<input type="checkbox"/>	Visually check the front fork and rear shock absorber seals	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check brake and clutch fluid level	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Change brake and clutch fluid				24
<input type="checkbox"/>	<input type="checkbox"/>	Check front and rear brake disc and pad wear. Replace, if necessary		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check the proper tightening of brake calliper bolts and front and rear brake disk screws		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check front and rear wheel nuts and rear sprocket nut tightening		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check frame-to-engine, frame-to-swinging arm and frame-to-rear shock absorber fasteners tightening		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check front and rear wheel hub bearings and steering tube bearing clearance		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check the cush drive damper on rear sprocket and lubricate the rear wheel shaft		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check chain, rear sprocket and sprocket wear and check final drive chain tension, lubrication and stretch. Measured slackening value: _____ (cm) NOTE: It is recommended to change the final drive chain kit within 20,000 km/12,000 mi.	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check the freedom of movement and tightening of the side stand	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check that all gaiters and visible hoses (i.e. fuel, brake and clutch, cooling system, bleed, drain hoses, etc.) are not cracked, are tight and properly housed	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check rear brake lever correct free play	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Lubricate the levers at the handlebar and pedal controls		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check the freedom of movement of side pannier tilt system and top case		•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check tyre pressure and wear	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check the operation of all electric safety devices (side stand and clutch sensor, front and rear brake switch, engine stop switch, gear/neutral sensor)	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Check lighting devices, turn indicators, horn and controls operation	•	•		•
<input type="checkbox"/>	<input type="checkbox"/>	Final test and road test of the motorcycle, testing safety devices (e.g. ABS, DTC and VHC), electric fans and idling	•	•	•	•
<input type="checkbox"/>	<input type="checkbox"/>	Visually check the coolant level and circuit for damage	•	•	•	•
<input type="checkbox"/>	<input type="checkbox"/>	Soft cleaning of the vehicle, service coupon registration with turning off of Service warning light on instrument panel with DDS 3.0 and filling in of the on-board documentation (Service Booklet)	•	•	•	•

The Oil Service 1000 must be performed after the first 1,000 km/600 miles or within 6 months from delivery of motorcycle to Customer.
 The Oil Service must be performed every 15,000 km/9,000 mi or every 24 months.
 The Valve Check must be performed every 60,000 km/36,000 mi.
 The Annual Service must be performed every 12 months.

Thank you! Your Ducati Technician: